



"WA" Profile

Armored Blockout Condition

Design Features

- Cost effective solutions for general construction
- Over 20 year history of success
- · High abrasion and ultra-violet resistance

Model	Groove Width "A"						Min. Install		Groove		Nominal			
Number	Min.		Max.		Total		Width		Depth "B"		Width		Height	
	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm
WA-162	.625	16	1.381	35	.756	19	1.000	25	2.125	54	1.625	41	1.625	41
WA-175	.688	17	1.488	38	.800	20	1.000	25	2.625	67	1.750	44	2.000	51
WA-200	.875	22	1.700	43	.825	21	1.250	32	2.625	67	2.000	51	2.000	51
WA-225	.953	24	1.913	49	.960	24	1.375	35	3.000	76	2.250	57	2.250	57
WA-250	1.000	25	2.125	54	1.125	29	1.500	38	3.563	90	2.500	64	2.500	64
WA-300	1.125	29	2.550	65	1.425	36	1.750	44	4.313	110	3.000	76	3.000	76
WA-350	1.375	35	2.975	76	1.600	41	2.250	57	4.438	113	3.500	89	3.500	89
WA-400	1.625	41	3.400	86	1.775	45	2.500	64	5.000	127	4.000	102	4.000	102
WA-500	1.687	43	4.250	108	2.563	65	3.000	76	5.938	151	5.000	127	5.000	127

Bridge Series Wabo®CompressionSeal



Watson Bowman Acme Corp. 95 Pineview Drive Amherst, NY 14228 phone: (716) 691-7566 fax: (716) 691-9239 www.wbacorp.com

		BASF
The	Che	mical Company

	1000
DETAILED BY:	DATE:
CTW	10/12/00
CHECKED BY:	CURRENT ISSUE:
WBA	2/2/10
SHEET NO:	DRAWING NO:
2	C-20513