



Note:
Recommended detail is to assist WBA's valued customers in addressing occasional project conditions. Detail is not provided with any implied, verbal or written watertight warranties.

Dimensional Chart		
Model	Evazote UV Size	Evazote P/n.
ME-225	2 1/2" x 2"	30622
ME-300	3 1/8" x 2 1/2"	30631
ME-400	4 1/16" x 3"	30641
ME-500	5" x 4"	30650
ME-600	N/A	Special order

Splicing Detail for Dissimilar Seal profiles ME to Evazote Transition

Installation Notes:

1. Contractor shall exercise care to make sure that the cuts on the Evazote and WaboCrete Membrane seal are square and true. This is required to ensure a good connection between the two seals during the splicing process.
2. When splicing the "ME" and dissimilar seal profiles to WaboEvazote, the top of the seal lug shall be flush with the top of Evazote.
3. Contractor shall apply "PP Primer" to the face of the WaboCrete Membrane that is going to be adhered to Evazote. After the "PP Primer" has dried the contractor shall apply Aron Alpha 241F to the WaboCrete Membrane only and apply pressure against the Evazote Seal for at least 60 seconds.
4. Apply tension to the splice line & apply additional 241F where splice line shows signs of minor separation.

Optional:

5. Apply low modulus sealant (By Others) at top junction of seal profiles.

PROJECT NAME:	-
PROJECT LOCATION:	-
DRAWING DESCRIPTION:	Wabo®Crete Membrane
DATE: 03/03/08	MODEL: ME



Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

Watson Bowman Acme Corp.
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.wbacorp.com



REVISION NO:	-
SHEET NO:	1
DRAWING NO:	A-25722