



ME-225
Slab to Slab Condition

Notes:

- 1.) Please refer to the installation guide for information on splices, terminations, transitions, and additional details concerning adjacent construction.
- 2.) Minimum and maximum values shown on dimension chart are the limits for proper system performance. Unless otherwise noted, the dimension shown at "A" Mid is the recommended installation joint opening.
- 3.) If required, please consult with a WBA representative for the types and quantities of any chemical components needed for proper installation.

() - DENOTES MILLIMETERS

DIMENSION CHART							
Model	* Part Number	"A" @ Min	"A" @ Mid	"A" @ Max	Total Movement	"D"	Shear Movement
ME-225	8825	3/4"(19)	1 3/8"(35)	2 1/4"(57)	1 1/2"(38)	1 3/8"(35)	± 3/4"(19)

(Standard Black Santoprene Seal)

Note: Minimum And Maximum Values Are After Movement Occurs. Mid Point Value Is The Recommended Size Of The Opening At Installation.

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:
Wabo®CreteMembrane
DATE: 09/21/16 MODEL: ME-225



Watson Bowman Acme Corp.
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.wbacorp.com



Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:
-

SHEET NO:
1

DRAWING NO:
S-10002