

() - Denotes Millimeters

DIMENSION CHART						
MODEL	"A" @ MIN	"A" @ MID	"A" @ MAX	"B" SYSTEM WIDTH	TOTAL MOVEMENT	
RFL-1000C	5-1/4"(134)	10"(254)	15"(381)	17-1/2"(445)	9-3/4"(248)	
RFL-1200C	6-1/4"(159)	12"(305)	18"(457)	20-1/2"(521)	11-3/4"(299)	
RFL-1800C	9-1/4"(235)	18"(457)	27"(686)	29-1/2"(749)	17-3/4"(451)	
RFL-2400C	12-1/4"(312)	24"(610)	36"(914)	38-1/2"(978)	23-3/4"(603)	

Note: Minimum And Maximum Values Are After Movement Occurs. Mid Point Value Is The Recommended Size Of Opening At Installation.

PROJECT NAME:

PROJECT LOCATION:

DRAWING DESCRIPTION:

Wabo®RoofCover

DATE: 12/14/06 MODEL: RFL-C



Watson Bowman Acme Corp. 95 Pineview Drive Amherst, NY 14228 phone: (716) 691-7566 fax: (716) 691-9239 www.wbacorp.com

Watson Bowman Acme

REVISION NO:

SHEET NO:

3

DRAWING NO:

C-96014

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of
Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is
strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are
provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All
technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and
is used at the Users own risk.