



NBS-1800C thru NBS-2400C

Note:

Suggested Inlay material for NBS-1800C and NBS-2400C is sheet vinyl. Other materials will require adjustment in slide plate thickness.

Model	"A" Min	"A" Mid	"A" Max	"B"	SW @ "A" Mid	Total Thermal Movement	Total Seismic Movement	"T"
NBS-1800C	9 1/4"(235)	18"(457)	23 1/4"(591)	9"(229)	25 11/16"(652)	1 1/4"(32)	14"(356)	1/16"(2)
NBS-2400C	12 1/4"(311)	24"(610)	30 1/2"(775)	10"(254)	33 3/16"(843)	1 1/4"(32)	18 1/4"(464)	1/16"(2)

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

Wabo®SeismaxPlus II Floor

DATE: 12/18/06

MODEL: NBS-C



We create chemistry

Watson Bowman Acme Corp.
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.wbacorp.com



Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:

-

SHEET NO:

5

DRAWING NO:

S-10007