



- NOTE:
1. BACKER ROD AT SEALANT LOCATIONS NOT SHOWN FOR CLARITY. BACKER ROD BY OTHERS.
 2. TOTAL THERMAL MOVEMENT CAPABILITY OF 2 COMPONENT POLYURETHANE SEALANT IS 5/8" (TYPICAL ALL MODEL SIZES)
 3. ENHANCED MOVEMENT CAPABILITIES AVAILABLE.

Note: Exposed Aluminum Surfaces Mill Finish (standard).

Model	Joint Opening (J.O.)						Total Seismic Movement		S.W.		B	
	at install		allow min.		allow max.				at install		(min)	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm		
SPJ-400C	4	100	2	51	5	127	3	76	8 7/16	214	6	152
SPJ-600C	6	152	2	51	7 1/2	191	5 1/2	140	10 7/16	265	6	152
SPJ-800C	8	203	2	51	10	254	8	203	13 7/16	341	7	178
SPJ-1000C	10	254	2	51	12 1/2	318	10 1/2	267	15 7/16	392	7	178
SPJ-1200C	12	305	2	51	15	381	13	330	17 15/16	456	7	178
SPJ-1600C	16	406	2	51	20	508	18	457	22 15/16	583	8	203
SPJ-1800C	18	457	2	51	22 1/2	572	20 1/2	521	26 7/16	672	10	254

Note: J.O. minimum and maximum values are after seismic movement occurs.

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION: **Wabo®SeismicPan**

DATE: 12/14/06 MODEL: SPJ-C



Watson Bowman Acme Corp.
 95 Pineview Drive Amherst, NY 14228
 phone: (716) 691-7566 fax: (716) 691-9239
 www.wbacorp.com



Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO: -

SHEET NO: 2

DRAWING NO: C-18331