

## WABO® URE PLATE PRIMER

Version 1.1

07/26/2006

### 1. PRODUCT AND COMPANY INFORMATION

Company : **Watson Bowman Acme Corporation**  
 95 Pineview Drive  
 Amherst, NY 14228

Telephone : 716-691-7566

Emergency telephone number : (800) 424-9300  
 (703) 527-3887 (Outside Continental US)

Product name : WABO® URE PLATE PRIMER

MSDS ID No. : 11602

TSCA Inventory : All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Canadian DSL : All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).

### 2. HAZARDOUS INGREDIENTS

<u>Chemical</u>	<u>CAS No.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	<u>Weight %</u>
ISOPROPANOL	67-63-0	200 ppm	400 ppm	400 ppm	N.E.	60.00 - 100.00 %

### 3. HAZARDS IDENTIFICATION

HMIS® Rating : HEALTH 2 FLAMMABILITY 3 PHYSICAL HAZARD 0

WHMIS Class : D2B  
 B2

Primary Routes of Entry : Ingestion  
 Inhalation  
 Eye contact  
 Skin contact

#### Effects of Overexposure

Inhalation : Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations can cause CNS-depression and narcosis. Prolonged inhalation can be harmful.

Skin : Prolonged skin contact may defat the skin and produce dermatitis. Prolonged or repeated exposure can cause skin irritation and redness.

Eyes : Can cause slight irritation, redness, tearing and blurred vision.

Ingestion : Intake can cause gastrointestinal irritation and nausea.

Chronic exposure : This product contains solvents. Reports associate repeated and prolonged occupational

## WABO® URE PLATE PRIMER

Version 1.1

07/26/2006

overexposure to solvents with permanent brain and nervous system damage. Reports also indicate that solvents cause liver damage, kidney damage, and mucous membrane irritation. Be warned that intentional misuse by deliberately inhaling the vapors and/or the product contents (a process often called "sniffing") can be harmful or fatal.

### Carcinogenicity

	ACGIH	IARC	NTP	OSHA
ISOPROPANOL	Not classifiable as a human carcinogen.	Sufficient data.	N.E.	N.E.

## 4. FIRST AID MEASURES

- Eye contact : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
- Skin contact : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
- Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.
- Inhalation : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

## 5. FIRE-FIGHTING MEASURES

- Flash point : 54.9 °F (12.7 °C)
- Autoignition temperature : 662 °F (350 °C)
- Lower explosion limit : no data available
- Upper explosion limit : no data available
- Suitable extinguishing media : carbon dioxide (CO<sub>2</sub>)  
foam  
dry chemical  
water fog
- Fire and Explosion Hazards : Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; CONTAINERS MAY EXPLODE AND CAUSE INJURY OR DEATH. Heating can release vapours which can be ignited. Solid stream of water or foam can cause frothing.
- Special Fire-fighting Procedures : Can be ignited by heat, sparks or flame. At higher temperature pressure build up in sealed containers. Use water to cool containers exposed to fire. As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

## WABO® URE PLATE PRIMER

Version 1.1

07/26/2006

### 6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up : Ventilate the area and remove all sources of ignition. Evacuate unnecessary personnel. Take action to eliminate source of leak. Large spills should be handled carefully. Put on respiratory protection and necessary personal protective equipment. Dike or impound spilled Liquid. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### 7. HANDLING AND STORAGE

Handling : Keep out of reach of children. Use only in area provided with appropriate ventilation. Take precautionary measures against static discharges. Ground and bound containers when transferring material. For personal protection see section 8.

Storage : Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep container tightly closed.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Eye protection : Wear as appropriate:  
safety glasses with side-shields  
goggles  
face-shield

Hand protection : Wear Chemically resistant gloves.

Body Protection : Wear as appropriate:  
Chemically resistant clothes  
preventive skin protection

Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.

Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.

Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Color : clear

Physical State : liquid

Odor : acetone-like

pH : not applicable

Odor Threshold : no data available

**WABO® URE PLATE PRIMER**

Version 1.1

07/26/2006

Vapor Pressure	:	30.003 mm/Hg at 68 °F (20 °C)
Vapor Density	:	no data available
Boiling point/range	:	355.60 - 356.9 °F (179.78 - 180.5 °C)
Freeze Point	:	<32 °F (0 °C)
Water solubility	:	completely soluble
Specific Gravity	:	0.787
Viscosity	:	no data available
Evaporation rate	:	no data available
Partition coefficient (n-octanol/water)	:	no data available
VOC Concentration as applied (less water and exempt solvents)	:	772 g/l

**10. STABILITY AND REACTIVITY**

Stability	:	Stable under recommended storage conditions.
Conditions to avoid	:	Heat, flames and sparks. Direct sources of heat. Strong sunlight for prolonged periods. Prolonged exposure to high temperatures
Materials to avoid	:	strong oxidizing agents amines Aldehydes ammonia chlorinated compounds
Hazardous decomposition products	:	carbon oxides
Hazardous polymerization	:	Will not occur under normal conditions.

**11. TOXICOLOGICAL INFORMATION**

**Acute inhalation toxicity**

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>	<u>Exposure time</u>
	LC50	no data available		
<u>Component</u>				
ISOPROPANOL	LC50	no data available		

**WABO® URE PLATE PRIMER**

Version 1.1

07/26/2006

**Acute oral toxicity**

	Type	Value	Species
<u>Product</u>	LD50 (Oral)	no data available	
<u>Component</u>			
ISOPROPANOL	LD50 (Oral)	3,160 mg/kg	

**Acute dermal toxicity**

	Type	Value	Species
<u>Product</u>	LD50 (Dermal)	no data available	
<u>Component</u>			
ISOPROPANOL	LD50 (Dermal)	no data available	

**12. ECOLOGICAL INFORMATION**

Ecotoxicological Information : There is no data available for this product.

**13. DISPOSAL CONSIDERATIONS**

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

**14. TRANSPORT INFORMATION**

DOT	: Proper shipping name	ISOPROPANOL
	UN-No	<b>1219</b>
	Class	3
	Packaging group	II
	Primary Label	Flammable liquid
IATA	: Proper shipping name	ISOPROPANOL
	UN-No	<b>1219</b>
	Class	3
	Packaging group	II
	Primary Label	Flammable liquid

**15. REGULATORY INFORMATION**

**SARA 311/312 (RTK)**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD FIRE HAZARD DELAYED (CHRONIC) HEALTH HAZARD

**SARA 313**

**WABO® URE PLATE PRIMER**

Version 1.1

07/26/2006

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Weight %</u>	<u>CAS No.</u>	<u>Chemical Name</u>
60.00 - 100.00 %	67-63-0	ISOPROPANOL

**CERCLA**

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
100 lbs	67-63-0	ISOPROPANOL

**TSCA Section 12(b) Export Notification**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no TSCA 12(b) Chemicals in this product.

**California Proposition 65**

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

<u>CAS No.</u>	<u>Chemical Name</u>
----------------	----------------------

There are no Proposition 65 chemicals known to exist in this product.

---

**16. OTHER INFORMATION**

---

- Legend : N.E. - Not Established  
TLV - Threshold Limit Value  
STEL - Short Term Exposure Limit  
PEL - Permissible Exposure Limit  
CEIL - Ceiling
- Prepared By : Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.